



Quicher Precision Screw Feeder

Quicher alone can cope with various types of screws. Automatic screw feeder with the world's first replaceable rail. With Quicher, it is easy to rearrange the production line to meet the change of screw diameter. It also helps you to improve the quality control and productivity.

[NS SERISE]

MODEL NAME & NUMBER	NSB	NSR
SIZE(mm)	123(W)×181 (D) ×145 (H)	123(W)×181 (D) ×145 (H)
WEIGHT(INCLUDING RAIL)	APPROX. 2.92Kg	APPROX. 3.01Kg
POWER SOUCE	AC 100V, DC 12V 500mA, AC ADAPTER	
PROTECTION & RECOVERY CIRCUIT	MOTOR OVERLOAD STOP.PROTECTION CIRCUIT FOR REVERSE POWER CONNECTION	
APPLICABLE SCREW	FROM M1.0 TO M3.0 (TO THE TABLE FOR APPLICABLE RAILS)	
APPLICABLE SCREW LENGTH (UNDER HEAD)	UP TO 20mm	
SCOOPING CHAMBER CAPACITY	80cc	
ACCESSORIES (IN PACKAGE)	INSTRUCTION MANUAL ALLEN WRENCH(L SHAPED,2mm) AC ADAPTER PASSAGE WINDOW(EACH OF TWO TYPES) 0.35mm GAUGE PLATE(TO ADJUST HOLDING PLATE)	INSTRUCTION MANUAL ALLEN WRENCH(L SHAPED,2mm) AC ADAPTER PASSAGE WINDOW(EACH OF TYPES)

Pactumax International Pte Ltd

39, Kaki Bukit View, Singapore 415968, Tel: 65 6482 5006, Fax: 65 6482 5703

Email: sales@pactumax.com, Website: www.pactumax.com

[NSB SERISE]

SCREW NOMINAL SIZE	M1.0	M1.2	M1.4	M1.7	M2.0	M2.3	M2.6	M3.0
APPLICABLE RAIL	SR10	SR12	SR14	SR17	SR20	SR23	SR26	SR30

[NSR SERISE]

SCREW NOMINAL SIZE	M1.0	M1.2	M1.4	M1.7	M2.0	M2.3	M2.6	M3.0
APPLICABLE RAIL	SRR10	SRR12	SRR14	SRR17	SRR20	SRR23	SRR26	SRR30

When you place an order, please specify the type number of the applicable rail. NS series can cope with the screw size from M1.0 to M3.0.