









## Material

Tough-yet-flexible chrome-vanadium molybdenum steel, through-hardened, bronzed.

## Application

Simply hammer in the extractor, position the ring spanner to the bottom and screw out without tilting. For thread-conserving removal of damaged or broken-off screws with left-hand or right-hand thread, particularly stripped hex screws.

Order-No.	EAN				
03847	4010995038472	2,0	85	6	18
03848	4010995038489	2,5	85	6	18
03849	4010995038496	3,0	85	6	18
03850	4010995038502	4,0	85	6	19
03851	4010995038519	5,0	85	6	19
03852	4010995038526	6,0	95	8	39
03853	4010995038533	8,0	95	10	60
03854	4010995038540	10,0	110	12	100

Order-No.	EAN					
01310	4010995013103	T6	41	18	2,5	2
01311	4010995013110	T7	44	18	2,5	2
01312	4010995013127	T8	47	18	2,5	2
01313	4010995013134	T9	51	19	3	3
01314	4010995013141	T10	54	20	3	3
01315	4010995013158	T15	57	22	3,5	5
01316	4010995013165	T20	62	23	4	7
01317	4010995013172	T25	67	25	4,5	9
01318	4010995013189	T27	72	27	5,5	15
01319	4010995013196	T30	79	30	6	20
01320	4010995013202	T40	86	33	7	30
01321	4010995013219	T45	90	36	8	420
01322	4010995013226	T50	104	41	9	61
01323	4010995013233	T55	120	47	12	121
01324	4010995013240	T60	134	52	14	183
03764	4010995037642	T5	39	18	2,5	1