



## **Product description**

The fully certified TorqueVario®-S VDE torque system provides controlled screw tightening combined with safe use for electric installations. The tool set contains an ergonomically shaped torque screwdriver with an integrated numeric scale, 15 slimBits, a bit holder and an adjusting tool. All components are arranged practically in a high-grade, hard-wearing bag, where they are easy to identify. The VDE torque screwdriver covers a wide variety of applications with a torque range between 0.8 and 5.0 Nm. A clearly audible, physically perceptible signal emitted when the torque is produced guarantees process safe torque mechanics, protecting against damage to materials and eliminating the need for retouching. With a release accuracy of +/- 6%, the torque tool complies with EN ISO 6789 requirements. The insulated ClicFix bit holder guarantees a secure hold for 75 mm long slimBits thanks to mechanical blade locking. Both the torque screwdriver and the slimBits undergo an individual piece test as per the international IEC 60900 standard, allowing users to work safely on live parts up to 1,000 V AC.

## **Handle**

Bit holder with SoftFinish® electric multi-component handle.

## **Standard**

DIN EN ISO 6789. Manufactured acc. to IEC 60900.

#### **Extra**

Effortless access to low-lying fastening elements. Arranged clearly in a high quality, rugged and durable bag.

# **Application**

For controlled fastening on live parts up to 1 000 V AC.

## Bit chuck

Insulated metal bit holder holds all slimBits reliability.

## **Bits**

Protective insulation moulded directly onto the bit and completely integrated into the bit in the lower area. Individually tested protective insulation 1,000 V AC, VDE and GS tested.

Order-No.	EAN	Nm	<b>7</b> ∕4%	0	<b>.</b>	÷	J g J
26626	4010995266264	0,8 - 5	6 %	3,8	138	36	285
26627	4010995266271	2 - 7	6 %	3,8	142	41	352
26625	4010995266257	0,5 - 2	6 %	3,8	131	30	256

