



Application

For controlled fastening of circular plug connectors with hexagonal head according to specified torque.

Order-No.	EAN	Nm	±%	⊙	↔	⊕	g
26925	4010995269258	0,4 Nm	6 %	4,0	112	23	69
26127	4010995261276	0,5 Nm	6 %	4,0	112	23	68
26047	4010995260477	0,6 Nm	6 %	4,0	112	23	69
26327	4010995263270	0,8 Nm	6 %	4,0	112	23	69
26048	4010995260484	0,9 Nm	6 %	4,0	112	23	70
26133	4010995261337	1,1 Nm	6 %	4,0	119	30	124
26049	4010995260491	1,2 Nm	6 %	4,0	119	30	126
26901	4010995269012	1,5 Nm	6 %	4,0	119	30	124
26051	4010995260514	2,0 Nm	6 %	4,0	119	30	125
26128	4010995261283	2,5 Nm	6 %	4,0	119	36	125
26052	4010995260521	3,0 Nm	6 %	4,0	126	36	170
26129	4010995261290	3,8 Nm	6 %	4,0	126	36	172
26053	4010995260538	5,0 Nm	6 %	4,0	132	41	244
26130	4010995261306	5,5 Nm	6 %	4,0	132	41	247
34533	4010995345334	6,0 Nm	6 %	4,0	132	41	246
26131	4010995261313	7,2 Nm	6 %	4,0	132	41	247

