



Product description

Are you looking for controlled screw tightening without damage to materials and follow-up work? No problem with the easyTorque torque screwdriver, which ensures process safety in its application. Thanks to a click signal when reaching the set torque value, the work piece remains undamaged and protects you from warranty claims. The multi-component handle, which is ergonomically designed for the hand, enables optimum power transmission while protecting your health. In addition, the torque screwdriver can be quickly identified by an imprint on the end of the handle and is also compatible with all blades from the 2859 series. With its mechanics that are not affected by industrial lubricants, the torque screwdriver is your perfect companion for comfortable work. Designed based on the standard EN ISO 6789, the torque tool offers a release accuracy of +/- 10%.

Precision

±10%

Handle

Multi-component handle optimally designed for the hand enables optimal power transmission. Audible and perceptible click when the pre-set torque has been attained. Rapid identification with imprint on handle end. Mechanism insensitive to industrial lubricants. Compatible with all blades of the 2859.

Standard

Based on DIN EN ISO 6789.

Note

Bit holders or blades are not included in delivery.

Application

For applications where recommended torque settings are important. Use in combination with a Wiha torque interchangeable blade.

| Order-No. | EAN | Nm |  % |  |  |  |  |
|-----------|---------------|--------|---|---|--|--|--|
| 36229 | 4010995362294 | 0,5 Nm | 10 % | 4,0 | 130 | 34 | 95 |
| 36230 | 4010995362300 | 0,6 Nm | 10 % | 4,0 | 130 | 34 | 95 |
| 36240 | 4010995362409 | 0,9 Nm | 10 % | 4,0 | 130 | 34 | 94 |
| 36231 | 4010995362317 | 1,1 Nm | 10 % | 4,0 | 130 | 34 | 101 |
| 36233 | 4010995362331 | 1,2 Nm | 10 % | 4,0 | 130 | 34 | 99 |
| 36234 | 4010995362348 | 1,4 Nm | 10 % | 4,0 | 130 | 34 | 101 |
| 36235 | 4010995362355 | 2,0 Nm | 10 % | 4,0 | 130 | 34 | 101 |
| 36236 | 4010995362362 | 2,5 Nm | 10 % | 4,0 | 130 | 34 | 106 |
| 36237 | 4010995362379 | 3,0 Nm | 10 % | 4,0 | 130 | 34 | 104 |
| 36238 | 4010995362386 | 3,8 Nm | 10 % | 4,0 | 130 | 34 | 105 |
| 36320 | 4010995363208 | 4,0 Nm | 10 % | 4,0 | 130 | 34 | 105 |
| 36321 | 4010995363215 | 4,5 Nm | 10 % | 4,0 | 130 | 34 | 105 |
| 36239 | 4010995362393 | 5,0 Nm | 10 % | 4,0 | 130 | 34 | 105 |