



## Product description

Users risk damaging electronic components irreparably when working on them. Such problems become a thing of the past with the TorqueVario®-S ESD torque screwdriver set. The ESD torque screwdriver is manufactured in line with the IEC 61340-5-1 international standard and thus guarantees maximum protection for electronic components. The dissipative tool handle has a surface resistance between 10<sup>6</sup> and 10<sup>9</sup> ohm and safely channels electrostatic energy away in a controlled fashion. The torque screwdriver also ensures controlled screw tightening. Thanks to its integrated numeric scale and the supplied adjusting tool, variable torque settings can be made, therefore covering a wide application field. A clearly audible and tactile signal is emitted when triggering the set torque value, guaranteeing process-safe work, protecting material and eliminating follow-up work. With a release accuracy of +/- 6%, the torque tool complies with EN ISO 6789 requirements. The set includes a bit holder for 1/4" bits. The ESD torque screwdriver is also compatible with 4 mm Wiha Torque interchangeable blades (series 2859). All tools in the set are safely stored neatly away in a robust, clearly organised box.

## Precision

±6%, tracing to national standards (see table for other tolerances).

## Handle

Torque infinitely adjustable with Torque-Setter setting tool (also supplied). Ergonomic multi-component handle, made of ESD-safe dissipative material. Handle sizes proportioned to optimise torque setting. Audible and perceptible click when the pre-set torque has been attained. Surface resistance 10<sup>6</sup> - 10<sup>9</sup> ohms. Compatible with all blades of the 2859.

## Standard

DIN EN ISO 6789. IEC 61340-5-1.

## Extra

Delivered in practical plastic box, incl. factory calibration certificate.






## Application

For controlled fastening at a specific torque on components susceptible to electrostatic discharge.

**Pactumax International Pte Ltd**

39, Kaki Bukit View, Singapore 415968, Tel: 65 6482 5006, Fax: 65 6482 5703

Email: sales@pactumax.com, Website: www.pactumax.com

Order-No.	EAN	Nm		 %			
36851 *	4010995368517	0,04 - 0,46	23	10 %	4,0	127	138
36852 *	4010995368524	0,1 - 0,6	23	6 %	4,0	127	137
26865 *	4010995268657	0,1 - 0,6	23	10 %	4,0	127	141
26629 *	4010995266295	0,4 - 1	23	6 %	4,0	127	139
26866 *	4010995268664	0,5 - 2	30	6 %	4,0	131	189
30495 *	4010995304959	0,8 - 5	36	6 %	4,0	138	238